Cuprofit Range



Conex | Bänninger
Cuprofit

Conex Bänninger Cuprofit Push-fit range is simple to install, demountable and re-useable. The Push-fit concept eliminates the need for flames or flux on site, thus avoiding numerous health and safety issues and saving substantial time during installation. Cuprofit offers a leak-proof, tamper resistant and demountable connection. Cuprofit is available in sizes 10, 15, 22 and 28mm.

Conex Bänninger Cuprofit Push-fit fittings are manufactured from copper or DZR brass bodies and incorporate an EPDM O-ring and Stainless Steel grab ring. Conex Cuprofit fittings are designed for hard, half-hard and soft copper tubes.

Applications & Technical Information	
Drinking water	Y
Sanitary water	Y
Heating and chilled water systems	Y
Available Sizes	10, 15, 22, 28
Warranty	25 Years
Operating Parameters	16 bar @ 0-30°C 10 bar @ 65°C 7 bar @ 95°C
Material	Body: Copper or DZR O-Ring: EPDM Grab Ring: Stainless Steel
Water / Glycol	50/50 to -20°C
Disconnect and Reuse	x 20

For more details contact our technical team.

SALES: +44 (0)121 557 2831 FAX: +44 (0)121 520 8778 WEB: www.conexbanninger.com EMAIL: sales@ibpgroup.com

N746 Draining Tap

Plain Tail (Male Copper)



ITEM	SIZE	PACK
N746 015000000	15mm	10

R720 Straight Servicing Valve

Push-Fit x Push-Fit



ITEM	SIZE	PACK
R720 015000000	15mm	2

R717 Straight Washing Machine Valve

Push-Fit x Male Thread



ITEM	SIZE	PACK
R717 015006000	15 x 3/4"	1

Conex | Bänninger
Cuprofit

R204 Lever Ball Valve

Push-Fit x Male Thread



ITEM	SIZE	PACK
R204 022000000	22mm	1

R850 S850 Release Tool



ITEM	SIZE	PACK
S850 022015010	22 x 15 x 10mm	1
R850 022015010	22 x 15 x 10mm	1