

Snap On

- Manufactured from premium grade white polymer
- Low temperature impact resistance
- High temperature tensile strength
- Working temperature range -10˚C to +80˚C

Spacers

- Are the most effective way of fitting pipework insulation as required by water bye-law 49
- Fit all clips and will increase the wall clearance from 12mm to 25mm
- Can be stacked and each additional spacer gives 13mm more clearance

Range Information

Product Code	Size mm	Unit Qty
120-270-005	15 Single	100
120-270-010	22 Single	100
120-270-015	28 Single	50
120-275-020	Spacers	100



Clip Lock

- Heat stabilised white polypropylene clips
- Large base design
- High stand off allows for lagging and heat circulation
- Hinge design for repeated opening and closing
- Working temperature range up to 110˚C

Spacers

- Comply with British Water supply bye-law 49
- Provides clearance for lagging up to 30mm thick

Range Information

Product Code	Size mm	Unit Qty
120-285-010	15 Single	100
120-285-020	22 Single	50
120-285-030	28 Single	25
120-285-040	15 Spacers	100
120-285-050	22 Spacers	100
120-285-060	15 Double	25
120-285-070	22 Double	25



Hinged Lock

- White polypropylene pipe clips
- Central hole fixing for both single and double clips
- Can be assembled together using the unique locking mechanism
- Special hinge reduces the risk of stress cracking
- Working temperature range -10˚C to +80˚C

Spacers

- Are the most effective way of fitting pipework insulation as required by water bye-law 49
- Will increase the wall clearance by 22mm

Range Information

Product Code	Size mm	Unit Qty
120-295-005	15 Single	100
120-295-010	22 Single	100
120-295-015	28 Single	50
120-295-020	15 Double	50
120-295-025	22 Double	25
120-295-040	Spacers	100