

ART 26

DZR Brass Double Regulating Valve (DRV)

• 20 Bar Rated • -10°C to +120°C • BSP Parallel Ends (ISO 7/1) • EPDM Seat • 5 Year Guarantee • Conforms to BS 7350 / BS5154

	F		F
½"L	68	1¼"	108
½"	68	1½"	116
¾"	77	2"	143
1"	91		



ART 26 PRS

DZR Brass Double Regulating Valve (DRV) Press Ends

• 20 Bar Rated (15mm - 28mm) • 17 Bar Rated (35mm - 54mm) • -10°C to +120°C • Universal M + V Profile 15mm to 35mm • Dedicated M Profile 42mm and 54mm • EPDM Seat • 5 Year Guarantee

	F		F
15mm	118	42mm	185
22mm	136	54mm	227
28mm	148		
35mm	164		



ART 27

DZR Brass Orifice Plate (OP)

• 20 Bar Rated • -10°C to +120°C • BSP Parallel (½"), Taper (¾" - 2") M/F Ends (ISO 7/1) • 5 Year Guarantee • Conforms to BS7350

	F		F		F
½"UUL	67	½"	67	1½"	71
½"UL	67	¾"	67	2"	80
½"L	67	1"	64		
½"M	67	1¼"	71		



ART 28

DZR Brass Variable Orifice Double Regulating Valve (VODRV)

• 25 Bar Rated • -10°C to +120°C • BSP Parallel Ends (ISO 7/1) • 5 Year Guarantee • Conforms to BS7350 / BS5154 • WRAS Approved

	F		F
½"	77	1½"	115
¾"	80	2"	124
1"	87		
1¼"	108		



ART 250 PN16

Ductile Iron Double Regulating Valve (DRV) / (VODRV)

• 16 Bar Rated • -20°C to +120°C • Flanged PN16 • C/W Ext & Test Points for Variable Orifice Double Regulating Valve but not fitted • Conforms to BS5152 / BS7350

	F		F		F
2"	230	5"	400	12"	850
2½"	290	6"	480		
3"	310	8"	600		
4"	350	10"	730		



ART 250 PN25

Ductile Iron Double Regulating Valve (DRV) / (VODRV)

• 25 Bar Rated • -20°C to +120°C • Flanged PN25 • C/W Ext & Test Points for Variable Orifice Double Regulating Valve but not fitted • Conforms to BS5152 / BS7350

	F		F		F
2"	230	5"	400	12"	850
2½"	290	6"	480		
3"	310	8"	600		
4"	350	10"	730		

10" and 12" subject to factory lead time.