

ART 36

DZR Brass Double Check Valve BSP Parallel F/F Ends (ISO 228/1)

• 16 Bar Rated • -10°C to +85°C • Conforms with EN13959 • Suitable for Fluid Categories 1, 2 & 3 • WRAS Approved

	F		F
½"	71	1½"	134
¾"	83	2"	173
1"	98		
1¼"	118		



ART 37

DZR Brass Double Check Valve Compression Ends (BS EN1254-2)

• 10 Bar Rated • -10°C to +85°C • Conforms with EN13959 • Suitable for Fluid Categories 1, 2 & 3 • WRAS Approved

	F
15mm	79
22mm	100
28mm	112



ART 237

PN16 Ductile Iron Flanged Double Check Valve

• 16 Bar Rated • -10°C to +85°C • WRAS Approved

	F		F		F
2"	203	5"	403	12"	823
2½"	243	6"	463		
3"	283	8"	579		
4"	343	10"	711		



ART 236

PN16 Ductile Iron Flanged Double Check Valve

• 16 Bar Rated • -10°C to +23°C • WRAS Approved

	F		F
2"	205	5"	405
2½"	245	6"	465
3"	265		
4"	315		



ART 384

Bronze Swing Check Valve BSP Taper F/F Ends (ISO 7/1)

• 20 Bar Rated • -10°C to +232°C • Metal Seat • WRAS Approved

	F		F
½"	56	1½"	110
¾"	71	2"	129
1"	80		
1¼"	97		



ART 194 PRS

Brass Swing Check Valve Press Ends

• 16 Bar Rated • -10°C to +150°C • Universal M + V Profile 15mm to 35mm • Dedicated M Profile 42mm and 54mm • EPDM Seat • 5 Year Guarantee

	F		F
15mm	111	42mm	172
22mm	130	54mm	208
28mm	142		
35mm	156		