

ART 145

Ductile Iron Lugged and Tapped Butterfly Valve

• 16 Bar Rated • 0°C to +90°C • NBR Liner • DI Zinc Plated Disc • ISO Direct Mount • To suit PN16 Flanges only

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55		
3"	45	8"	60		
4"	51	10"	65		

Gearbox available. 8", 10" & 12" c/w gearbox as standard. Larger sizes available on request.



ART 145GB

Ductile Iron Lugged and Tapped Butterfly Valve c/w Gearbox

• 16 Bar Rated • 0°C to +90°C • NBR Liner • DI Zinc Plated Disc • ISO Direct Mount • To suit PN16 Flanges only

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55		
3"	45	8"	60		
4"	51	10"	65		



ART 115

Ductile Iron Wafer Butterfly Valve

• 16 Bar Rated • -10°C to +110°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • WRAS Approved • To suit PN10, PN16 and ANSI CLASS 150 flanges

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55		
3"	45	8"	60		
4"	51	10"	65		

Gearbox available. We strongly advise gearbox on all 8", 10" and 12" valves.



ART 125

Ductile Iron Wafer Butterfly Valve

• 16 Bar Rated • -10°C to +120°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • To suit PN10, PN16 and ANSI CLASS 150 flanges

	F		F		F
2"	42	5"	54	12"	77
2½"	45	6"	56		
3"	45	8"	61		
4"	52	10"	66		

Gearbox available. We strongly advise gearbox on all 8", 10" and 12" valves.



ART 120

Ductile Iron Wafer Butterfly Valve

• 16 Bar Rated • 0°C to +90°C • NBR Liner • Stainless Steel Disc • ISO Direct Mount • To suit PN10, PN16 and ANSI CLASS 150 flanges

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55		
3"	45	8"	60		
4"	51	10"	65		

Gearbox available. We strongly advise gearbox on all 8", 10" and 12" valves.



GEARBOX CI / DI

Cast Iron / Ductile Iron Gearbox

• Gearbox CI to suit ART 125 and ART 140
• Gearbox DI to suit ART 115, ART 120, ART 135 and ART 145