

ART 255

Ductile Iron Flanged Fixed Orifice Double Regulating Valve (FODRV)

• 16 Bar Rated • -20°C to +120°C • Flanged PN16 • C/W Fitted Test Points and Ext loose • Conforms to BS5152 / BS7350

	F		F		F
2"	230	5"	400	12"	850
2½"	290	6"	480		
3"	310	8"	600		
4"	350	10"	730		



ART 270 PN16

Stainless Steel Orifice Plate (OP)

• 16 Bar Rated • -10°C to +120°C • Wafer Pattern • C/W Ext & Test Points • Conforms to BS7350

	F		F		F
2"	20	5"	20	12"	20
2½"	20	6"	20		
3"	20	8"	20		
4"	20	10"	20		



ART 270 PN25

Stainless Steel Orifice Plate (OP)

• 25 Bar Rated • -10°C to +120°C • Wafer Pattern • C/W Ext & Test Points • Conforms to BS7350

	F		F		F
2"	22	5"	22	12"	22
2½"	22	6"	22		
3"	22	8"	22		
4"	22	10"	22		



ART 299

Spare Test Point Set of two, one red tab, one blue tab

ART 298

Spare Test Point Set of two, one red tab, one blue tab C/W Stainless Steel Extension

• 35 Bar Rated • -10°C to +135°C • ART 299 available in 1/4" and 1/2" • ART 298 available in 1/4"



ART 32

DZR Brass Thermostatic Balancing Valve with Anti Legionella Device (ISO 7/1)

• 25 Bar Rated (Static) • Working temp 40°C to 60°C • Anti Legionella temp 70°C • Fluid: Water • WRAS Approved

	F
½"	77
¾"	80
1"	87



ART 20C

DZR Brass Pressure Independent Control Valve (PICV / PIBCV)

• 25 Bar Rated • -10°C to +120°C • BSPM Parallel (ISO 228/1) • ΔP range 16-400 kPa • 5 Year Guarantee • Union Tail Pieces & Gaskets req'd (2 per valve for BSP male connection)

DN	F	Flow (l/s)
10	53	0.012-0.097
15	65	0.024-0.134
20	82	0.042-0.250
25	104	0.076-0.447

DN10-15 available in Low & High Flow variants.