

ART 642

Gunmetal Safety Valve BSP Parallel Female Ends (ISO 228/1)

• 16 Bar Rated • -50°C to +195°C • EPDM Diaphragm • WRAS Approved • PED 2014/68/EU

	F		F
½"	35	1½"	58
¾"	42	2"	68
1"	45	2½"	80
1¼"	47		



ART 645

Gunmetal High Discharge Safety Valve BSP Parallel Female Ends (ISO 228/1)

• 16 Bar Rated • -50°C to +195°C • EPDM Diaphragm • WRAS Approved • PED 2014/68/EU

	F		F
½"	36	1½"	68
¾"	43	2"	80
1"	47		
1¼"	58		



ART 642 FL

Gunmetal Safety Valve DIN Flange PN16 x BSP Parallel Female Ends (ISO 228/1)

• 16 Bar Rated • -50°C to +195°C • EPDM Diaphragm • WRAS Approved

	F		F
1"	45	2½"	80
1¼"	47		
1½"	58		
2"	68		

This product is subject to a lead time.



ART 645 FL

Gunmetal Safety Valve DIN Flange PN16 x BSP Parallel Female Ends (ISO 228/1)

• 16 Bar Rated • -50°C to +195°C • EPDM Diaphragm • WRAS Approved

	F
1"	47
1¼"	58
1½"	68
2"	80

This product is subject to a lead time.



ART 655

Cast Iron High Discharge Safety Valve Flanged Ends (DIN EN 1092)

• 25 Bar Rated • -10°C to +120°C • EPDM Bellows

	F		F		F
1/2"	80	1.1/2"	115	4"	180
3/4"	95	2"	120		
1"	100	2.1/2"	140		
1.1/4"	110	3"	160		

This product is subject to a lead time.



ART 705 - EasyFlow

Bronze Valve Assembly with Insulation Jacket BSP Parallel Female Ends (ISO 228/1)

• 16 Bar Rated • Outlet Pressure Range 1.5 - 6 Bar • Preset at 3 bar • +4°C to +80°C • WRAS Approved

	F
¾"	381.5
1"	373.5