

ART 135 PN16

Ductile Iron Lugged and Tapped Butterfly Valve

• 16 Bar Rated • -10°C to +110°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • WRAS Approved • To suit PN16 Flanges only

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55		
3"	45	8"	60		
4"	51	10"	65		

Gearbox available. We strongly advise gearbox on all 8", 10" and 12" valves.



ART 135GB PN16

Ductile Iron Lugged and Tapped Butterfly Valve c/w Gearbox

• 16 Bar Rated • -10°C to +110°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • WRAS Approved 2" - 12" only • To suit PN16 Flanges only

	F		F		F
2"	41	5"	54	12"	76
2½"	44	6"	55	14"	78
3"	45	8"	60	16"	102
4"	51	10"	65	18"	114

Sizes 14", 16" and 18" are not WRAS approved.



ART 135 PN25

Ductile Iron Lugged and Tapped Butterfly Valve

• 25 Bar Rated • -10°C to +110°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • WRAS Approved • To suit PN25 Flanges only

	F		F		F
2"	43	5"	56	12"	78
2½"	46	6"	56		
3"	46	8"	60		
4"	52	10"	68		

Gearbox available. 8", 10" & 12" c/w gearbox as standard.



ART 135GB PN25

Ductile Iron Lugged and Tapped Butterfly Valve c/w Gearbox

• 25 Bar Rated • -10°C to +110°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • WRAS Approved • To suit PN25 Flanges only

	F		F		F
2"	43	5"	56	12"	78
2½"	46	6"	56		
3"	46	8"	60		
4"	52	10"	68		



ART 140

Ductile Iron Lugged and Tapped Butterfly Valve

• 16 Bar Rated • -10°C to +120°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • To suit PN16 Flanges only

	F		F		F
2"	42	5"	54	12"	77
2½"	45	6"	56		
3"	45	8"	61		
4"	52	10"	66		

Gearbox available. We strongly advise gearbox on all 8", 10" and 12".



ART 140GB

Ductile Iron Lugged and Tapped Butterfly Valve c/w Gearbox

• 16 Bar Rated • -10°C to +120°C • EPDM Liner • Stainless Steel Disc • ISO Direct Mount • To suit PN16 Flanges only

	F		F		F
2"	42	5"	54	12"	77
2½"	45	6"	56	14"	77
3"	45	8"	61	16"	102
4"	52	10"	66	18"	114