GREENBROOK

Datasheet: PSKT2G

Weatherproof Accessories / Powerbreaker IP66 Range

Weatherproof IP66 2G Switched Socket



Technical Specification

Product Code	PSKT2G
Feature 1	Weatherproof to IP66
Feature 2	Can be used for long term projects
Feature 3	Suitable for all 13A BS plugs
Feature 4	5 Year Guarantee
Barcode	5012739643972
CE	Y
Colour	White Internal Unit - Grey & smoke Tinted Clear Lid Enclosure
Company DUNS Number	216156018
Country of Origin	China
Current (I)	13

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

Datasheet: PSKT2G

Finish body	Gloss
Fixings supplied with product	Cable Screws
Frequency (Hz) max	60
Frequency (Hz) min	50
Greenbrook Guarantee (Years)	5
HS Code	8536699099
Ingress Protection (IP)	IP66
Installation method	Surface mount
Knock-out Dimensions	20
Knock-out Qty	5
Materials Main Body	High Impact polycarbonate
Min Order Qty	1
Operating Temperature Range max C	40
Operating Temperature Range min C	-5
Pack Contents	1
Package Product Max. Length (mm)	180
Package Product Max. Height (mm)	85
Package Product Max. Width (mm)	136
Package Product Weight gross (g)	571
Product (only) Max. Depth (mm)	80
Product (only) Max. Height (mm)	130
Product (only) Max. Width (mm)	179
Product Weight net (g)	505
Sales Pack Qty	1
StatusCode	Active
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230
Wattage (W)	3000

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26