We connect and protect

# Macrofix Non-Insulated M8/M10, 83–93 mm OD, 3" Pipe, 80 DN

## CATALOG NUMBER

**MFN093EG**



## CERTIFICATIONS

## FEATURES


- Plastic washer prevents screws from falling out during installation
- Combo head bolt works with slotted, hex, or Phillips drivers
- Longer ears position the screw farther from the hanger, improving tool clearance when the screw is tightened
- Combination nut can be attached to M8 or M10 threaded rod, simplifying material handling
- Screw length has been optimized to accommodate an increased pipe range, reducing inventory

## PRODUCT ATTRIBUTES

- Article Number: 586111
- Material: Steel
- Finish: Electrogalvanized
- Outer Diameter (OD): 83 - 93 mm
- Pipe Size: 3"

| |
|---|
| NB/DN: 80 |
| Rod Size (RS): M8;M10 |
| Width (W): 23 mm |
| Thickness (T): 1.5 mm |
| Screw Diameter (Sc): 6 |
| Screw Length (L): 27mm |
| Static Load: 2000N |

## DIAGRAMS




## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

**Europe**
Netherlands:
+31 800-0200135
France:
+33 800 901 793

**Europe**
Germany:
800 1890272
Other Countries:
+31 13 5835404

**APAC**
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**



©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.