## Express Nails


**Zinc**

An underestimated rapid hammer-set anchor for concrete and masonry, ideal for interior timber-work such as battens and frames.







CONCRETE BRICK STONE



Drill required diameter hole



Hammer nail through fixture



28 - 150KG

**Technical Data**

| Substrate | Concrete ≥ 25N/mm² | | Fletton Brick 30N/mm² | | Cheshire Brick 45N/mm² | | Class B Eng. Brick 75N/mm² | |
|---|---|---|---|---|---|---|---|---|
| Size Ø (mm) | 6.0 | 8.0 | 6.0 | 8.0 | 6.0 | 8.0 | 6.0 | 8.0 |
| Drill Hole Ø (mm) | 6.0 | 8.0 | 6.0 | 8.0 | 6.0 | 8.0 | 6.0 | 8.0 |
| Fixture Clearance Hole Ø (mm) | 7.0 | 9.0 | 7.0 | 9.0 | 7.0 | 9.0 | 7.0 | 9.0 |
| Min. Embed. Depth (mm) | 30 | 40 | 30 | 40 | 30 | 40 | 30 | 40 |
| Min. Drill Hole Depth (mm) | 40 | 50 | 40 | 50 | 40 | 50 | 40 | 50 |
| Rec. Tensile Load (kN) | 0.52 | 1.50 | 0.48 | 0.61 | 0.29 | 0.53 | 0.28 | 0.62 |
| Max Rec. Load (kg) | 52 | 150 | 48 | 61 | 29 | 53 | 28 | 62 |

| Product Code | Size (mm) | MFT* (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---|---|---|---|---|---|
| **BOX** | | | | | |
| 00650EN | 6.0 x 50 | 20 | 200 | 16 | 384 |
| 00660EN | 6.0 x 60 | 30 | 100 | 15 | 540 |
| 00680EN | 6.0 x 80 | 50 | 100 | 15 | 540 |
| 00870EN | 8.0 x 70 | 30 | 100 | 18 | 432 |
| 00890EN | 8.0 x 90 | 50 | 50 | 35 | 840 |
| 08110EN | 8.0 x 110 | 70 | 50 | 15 | 540 |
| 08130EN | 8.0 x 130 | 90 | 50 | 15 | 540 |
| 08150EN | 8.0 x 150 | 110 | 50 | 12 | 324 |
| 08180EN | 8.0 x 180 | 140 | 50 | 12 | 288 |
| | | | | | EXN01 |
| **TIMBAG** | | | | | |
| 00660ENB | 6.0 x 60 | 30 | 90 | 5 | 600 |
| 00680ENB | 6.0 x 80 | 50 | 70 | 5 | 600 |
| 00890ENB | 8.0 x 90 | 50 | 45 | 5 | 600 |
| 08110ENB | 8.0 x 110 | 70 | 35 | 5 | 600 |
| 08150ENB | 8.0 x 150 | 110 | 30 | 5 | 600 |
| | | | | | BAG26 |
| **TIMPAC** | | | | | |
| 00660ENP | 6.0 x 60 | 30 | 8 | 5 | - |
| 00680ENP | 6.0 x 80 | 50 | 6 | 5 | - |
| 00890ENP | 8.0 x 90 | 50 | 6 | 5 | - |
| 08110ENP | 8.0 x 110 | 70 | 4 | 5 | - |
| 08130ENP | 8.0 x 130 | 90 | 6 | 5 | - |
| *MFT = MAX FIXTURE THICKNESS | | | | | PAK38 |

## Wirehangers

**Zinc**





CONCRETE

ALL STEEL NON-FLAMMABLE FIXING

Specifically designed for use in the suspended ceiling industry when securing suspension wires to concrete beams.

• Conforms to BS 7671:2018

188KG

**Technical Data**

| Substrate | Concrete ≥ 25N/mm² |
|---|---|
| Size Ø (mm) | 6.0 |
| Drill Hole Ø (mm) | 6.0 |
| Embedment Depth (mm) | 45 |
| Min. Embedment Depth (mm) | 50 |
| Rec. Tensile Load (kN) | 1.88 |
| Max Rec. Load (kg) | 188 |



Drill required diameter hole | Lightly tap the anchor into the hole | Set anchor using a claw hammer

| Product Code | Size Ø x L (mm) | Eye Ø (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---|---|---|---|---|---|
| **BOX** | | | | | |
| 0660WH | 6.0 x 60 | 6.3 | 100 | 16 | 640 |
| | | | | | WHG01 |

## Ceiling Anchors

**Zinc**






CONCRETE

A rapid light duty hammer-set anchor for attaching sheet metal, plastic or wood to concrete or masonry. Made from steel making it ideal for overhead applications.

72KG

**Technical Data**

| Substrate | Concrete ≥ 25N/mm² |
|---|---|
| Size Ø (mm) | 6.0 |
| Drill Hole Ø (mm) | 6.0 |
| Fixture Clearance Hole Ø (mm) | 6.5 |
| Min. Embedment Depth (mm) | 35 |
| Min Drill Hole Depth (mm) | 45 |
| Rec. Tensile Load (kN) | 0.72 |
| Max Rec. Load (kg) | 72 |



Drill required diameter hole | Insert fixing through attachment | Hammer wedge into anchor to secure

| Product Code | Size Ø x L (mm) | MFT (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---|---|---|---|---|---|
| **BOX** | | | | | |
| 0640CAM | 6.0 x 40 | 5 | 100 | 15 | 540 |
| 0665CAM | 6.0 x 65 | 30 | 100 | 8 | 384 |
| MFT = MAX FIXTURE THICKNESS. | | | | | CAM01 |

## Ceiling Angle Brackets

**Galvanised Steel**



Versatile bracket most commonly used for installing suspended ceiling systems. Various hole sizes allow different fixings to be used.

| Product Code | Size L x W x H (mm) | Hole Ø (mm) | T (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---|---|---|---|---|---|---|
| **BOX** | | | | | | |
| 25ABC | 25 x 25 x 22 | 4.5 & 7.0 | 1.0 | 100 | 18 | 864 |
| | | | | | | WHG03 |

CORROSION RATINGS Zinc | Yellow | Pre Galvanised ▸ **1** 2 3 4 5 Clean, dry & low humidity environments