



Exterior



POZI EN 14592:2008

NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above.

The silver organic coated C2 Exterior Strong-Fix provides exceptional corrosion resistance for use in harsh environments.
C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting. Its superior holding strength in a wide variety of materials provides ultimate performance.

- Ribs under head for improved countersinking
- Special plating to give 1,000 hours salt spray resistance
- Multi-layer coating consisting of organic top coat barrier and a zinc base layer
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting



Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
40030C2SBX	4.0 x 30	PZ2	200	75	1800
40040C2SBX	4.0 x 40	PZ2	200	50	1200
40050C2SBX	4.0 x 50	PZ2	200	35	840
40060C2SBX	4.0 x 60	PZ2	200	15	540
40070C2SBX	4.0 x 70	PZ2	200	15	540
50040C2SBX	5.0 x 40	PZ2	200	35	840
50050C2SBX	5.0 x 50	PZ2	200	15	540
50060C2SBX	5.0 x 60	PZ2	200	16	384
50070C2SBX	5.0 x 70	PZ2	200	16	384
50080C2SBX	5.0 x 80	PZ2	200	16	384
50100C2SBX	5.0 x 100	PZ2	100	15	540
60040C2SBX	6.0 x 40	PZ3	200	15	540
60050C2SBX	6.0 x 50	PZ3	200	16	384
60070C2SBX	6.0 x 70	PZ3	200	12	288
60100C2SBX	6.0 x 100	PZ3	100	15	540
TUB (C2 IMPACT POWER BIT INCLUDED)					
40030C2S	4.0 x 30	PZ2	400	12	360
40040C2S	4.0 x 40	PZ2	350	12	360
40050C2S	4.0 x 50	PZ2	300	12	360
40070C2S	4.0 x 70	PZ2	170	12	360
50040C2S	5.0 x 40	PZ2	200	12	360
50050C2S	5.0 x 50	PZ2	180	12	360
50060C2S	5.0 x 60	PZ2	150	12	360
50070C2S	5.0 x 70	PZ2	120	12	360
50080C2S	5.0 x 80	PZ2	110	12	360
50100C2S	5.0 x 100	PZ2	80	12	360
60040C2S	6.0 x 40	PZ3	150	12	360
60050C2S	6.0 x 50	PZ3	120	12	360
60070C2S	6.0 x 70	PZ3	90	12	360
60100C2S	6.0 x 100	PZ3	60	12	360
GRAB PACK (600 PCS)					
C2SGPACK	-	-	600	5	150
	4.0 x 30	PZ2	140		
	4.0 x 40	PZ2	100		
	4.0 x 50	PZ2	70		
	4.0 x 60	PZ2	60		
	5.0 x 40	PZ2	80		
	5.0 x 50	PZ2	55		
	5.0 x 60	PZ2	45		
	5.0 x 70	PZ2	30		
	5.0 x 80	PZ2	20		
	Impact 38mm Driver Bits	PZ2	3		



CC205

Exterior



TX DRIVE EN 14592:2008

The C2 Deck-Fix with a green organic coating ideal for outdoor projects.
C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting. Its superior holding strength in a variety of timber provides an ultimate performance.

- Strengthened head to prevent shearing when installed with an impact tool
- Ribs under the head for improved countersinking
- Helix shank for removing debris and to improve clamping
- Coated with a patented multi-layer corrosion resistant plating to withstand 1,000 hours salt spray
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
50C2D250BX	4.5 x 50	TX20	250	15	540
65C2D250BX	4.5 x 65	TX20	250	18	432
75C2D250BX	4.5 x 75	TX20	250	18	432
85C2D250BX	4.5 x 85	TX20	250	18	432
					IDD04
TUB (DRIVER BIT INCLUDED)					
50C2D250	4.5 x 50	TX20	250	8	288
65C2D250	4.5 x 65	TX20	250	8	288
65C2D1000	4.5 x 65	TX20	1,000	1	72
75C2D250	4.5 x 75	TX20	250	8	216
					IDD04
TIMBAG					
50C2DB	4.5 x 50	TX20	175	5	500
65C2DB	4.5 x 65	TX20	145	5	500
75C2DB	4.5 x 75	TX20	120	5	500
					BAG01
INDUSTRY PACK (1,000 PCS)					
65C2DIND	4.5 x 65	TX20	1,000	3	81
					IDD04







CORROSION RATINGS Exterior 1 2 **3** 4 5 Urban & industrial areas with a low salt atmosphere