
DATASHEET



CPL6CT

230V 6W CCT Adj Circular LED Panel- 140mm

www.mlaccessories.co.uk



MLA PART CODE	CPL6CT
DESCRIPTION	230V 6W CCT Adj Circular LED Panel- 140mm
NET WEIGHT (KG)	0.18
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 140 Projection - 15 Base Diameter - 94 Minimum Void - 50
CUT-OUT (MM)	Min./Max. Cut-out - 55 - 100
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	6
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	400/430/410
LUMENS LIGHT SOURCE ONLY (LM)	655
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	120.2
CIRCUIT WATTAGE (W)	5.49
CCT	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.046
DISPLACEMENT FACTOR	>0.5
SVM	0.049
PST-LM	0.04
BEAM ANGLE (DEGREES)	120

ML ACCESSORIES LTD

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832983910

Date Created: 08/01/2024 16:25

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.