CERTIFICATE

Certificate number: 2207728 (1)

Issued *26/07/2022*
Expires *26/07/2027*

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Ariston SpA.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.
Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.
See https://www.kiwa.com/gb/en/about-kiwa/water-products/ to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Ariston SpA
Viale Aristide Merloni 45
60044 Fabriano (AN)
ITALY

Product Certificate

Appendix to Certificate number: 2207728

The following products belong to this certificate

PRODUCT DESCRIPTION Range of electric water storage heaters, having an enamel lined storage tank, magnesium anode and pressure relief valve set at 6 bar. ATS3 – Without Production Surveillance.
MODEL(S) 3100306 New Europrisma 10 UR 2kW EU; 3100302 New Europrisma 10 OR 3kW EU; 3100303 New Europrisma 10 UR 3kW EU; 3100310 New Europrisma 15 UR 2kW EU; 3100308 New Europrisma 15 OR 3kW EU; 3100309 New Europrisma 15 UR 3kW EU; 3100306 New Europrisma 10 UR 2kW EU. 3100302 Andris Lux 10 OR 3kW EU; 3100303 Andris Lux 10 UR 3kW EU; 3100306 Andris Lux 10 UR 2kW EU; 3100308 Andris Lux 15 OR 3kW EU; 3100309 Andris Lux 15 UR 3kW EU; 3100310 Andris Lux 15 UR 2kW EU; 3100881 Andris Lux 10 OR 2kW EU; 3100882 Andris Lux 15 OR 2kW EU.
SIZE: ½” BSP(M).
SCOPE: Manufacturer recommended maximum working pressure 5.5 Bar & maximum operating temperature 74°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 74°C.
MARKING Ariston, model, serial no, pressure rating and ither technical information.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES Consideration must be made on installation to the airgap arrangement. The tundish supplied comply with the requirements of an air gap to drain.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements. A servicing valve shall be installed on the supply to the fitting in a readily accessible location.

Extra Notes