Wash Hand Basin Space Saver with Self-Closing Waste Valve

- Designed to allow full use of storage space below the basin within the cabinet or furniture
- The internal membrane opens under water pressure to allow discharge to flow freely and then closes to form a seal to prevent foul odour or sewer gas entering the building
- The valve allows air to be drawn into the discharge waste pipe when negative pressures occur and eliminates the need for secondary ventilation to the discharge pipework. This allows for greater flexibility in the plumbing design
- The valve can be easily cleaned without having to disassemble the discharge pipework. Simply remove the split pin at the front of the valve, take out the plug and membrane and clean in hot soapy water. Reassemble and relocate the split pin in the slot provided
- The WHB self-cleaning waste valve having no water seal can never dry out through evaporation or lack of use of the basin as the membrane seal remains closed
- Overall height 62mm
- Do not pour drain cleaner down this product





1¼" BSP female inlet nut x 1¼" universal compression outlet

Code	WHB-1

Tubular Traps with 75mm Water Seal



	1¼" Code	1½" Code	2" Code
Swivel 'P'	SA10	SC10	SE10



	1¼" Code	1½" Code	2" Code
Anti-Syphon (Silentrap)	SA10V	SC10V	SE10V



	1¼" Code	1½" Code	2" Code
Adjustable Inlet	ASA10	ASC10	ASE10



	1¼" Code	1½" Code	2" Code
Adjustable Inlet Anti-Syphon (Silentrap)	ASA10V	ASC10V	ASE10V

Tubular Traps with 75mm Water Seal



1¼" Code	1½" Code	2" Code

Adjustable Inlet Basin Trap with centre pin waste

ASA10W*	-	-



Low Inlet

BT3*	-	-



50mm Water Seal

BT4	-	-



Adjustable Inlet with connection for 19/23mm pipe

ASA10-SP*	**ASC10-SP***	-



Swivel 'S'

SB10	**SD10**	**SF10**



All One

SP10	**TP10**	**ZP10**



All One Anti-Syphon (Silentrap)

SP10V	**TP10V**	-



Running 'P'

SR10*	**TR10***	**SG10***



Running 'S'

SS10	**TS10**	**SH10**



1¼" Code	1½" Code	2" Code

Running suitable for most waste disposal units

-	**TT10***	-



Running with 20mm water seal

-	**TRSH10**	-



Adjustable Inlet with 19mm water seal

BT1	**BT2**	-



1¼" Code

Offset Basin Trap with adjustable inlet and cleaning eye

OBT1

Offset Anti-Syphon (Silentrap) Basin Trap with adjustable inlet and removable anti-syphon valve for cleaning purposes

OBT1V



Straight Through with one cleaning eye

1¼" Inlet x 1¼" outlet **X10**

Straight Through Anti-Syphon (Silentrap) with one cleaning eye

1¼" Inlet x 1¼" outlet **X10V**

Straight Through with two cleaning eyes

1¼" Inlet x 1¼" outlet **X10A**
1¼" Inlet x 1½" outlet **Y10**