
1½" Shower Traps with Top Access

Traps with Standard Waste and Flange

- Waste grid and dip tube removable from top to facilitate easy cleaning
- 70mm or 85mm standard waste and flange - white plastic, CP plastic or CP brass
- Gold plated wastes and grids only supplied as separate items - see page 29

	 70mm White Plastic Flange	 85mm White Plastic Flange	 70mm CP Plastic Flange
	**19mm Water Seal Trap with 1½" Universal Compression Outlet** Overall height 95mm	**STW1-R**	**STW5-R**	**STW3-R**
	**20mm Water Seal Trap with 1½" Solvent Weld Outlet Socket** Overall height 65mm	-	-	**STW4-65**
	**50mm Water Seal Trap with 1½" Multifit Outlet** Overall height 95mm	**STW2-95**	**STW6-95**	**STW4-95**
	**50mm Water Seal Resealing Trap with 1½" Multifit Outlet** Overall height 118mm	**STW2-R**	**STW6-R**	**STW4-R**
	**80mm Water Seal Resealing Trap with 1½" Multifit Outlet** Overall height 154mm	-	-	**STW10-R**

Do not pour drain cleaner down these products

	 85mm CP Plastic Flange	 70mm CP Brass Flange	 85mm CP Brass Flange
	STW7-R	**STW3-RB**	**STW7-RB**
	-	-	-
	STW8-95	**STW4B-95**	**STW8B-95**
	STW8-R	**STW4-RB**	**STW8-RB**
	-	-	-

Flow Rates

All McAlpine shower traps with top access surpass the minimum required flow rate when tested in accordance with clause 5 of BS EN 274-2:2002.

26 Litres per minute tested under a constant **15mm Head of Water**

52 Litres per minute tested under a constant **120mm Head of Water**

Code **STW4-R**

