PROFESSIONAL

Drainage | Testing



Hand Bellows Use to pump air into the pipe system being tested - fitted with a positive, hand operated non-return valve.

Code: **179O**



Nipple Caps Made from plastic with a washer. For attachment to drain test plug outlets to enable connection of rubber hose to a U gauge **(180S 1/2in.BSP / 181V 1in.BSP / 182Y 2in.BSP)**.

Code: **180S / 181V / 182Y**



U Gauge Tests for leaks in pipes up to 100mm wg pressure (10mb). Unbreakable parts. Hinged lid.

Code: **175C**




Drain Test Kit Use the kit to carry out an air test to 100mm wg pressure (10mb) on drain. Includes U Gauge, bellows pump, 1/2in.BSP & 1in.BSP nipple caps, T piece; 3 x 600mm lengths of rubber hose.

Code: **174Z**



Hose Adaptor Adaptor for connecting 5.5mm ID gas test gauge rubber hose to 10mm ID rubber hose used with drain test plugs and nipple caps.

Code: **AD01**



Tee Piece Connects three pieces of rubber hose 10mm ID together for convenient connection to U gauge, bellows and nipple cap.

Code: **183B**



Rubber Hose Correct diameter to connect U gauge components together. Colour Black. (**20m x Ø10mm**)

Code: **1445F**



Nylon Test Plugs Used for blocking off drain pipes and for air testing with 1/2in BSP outlet **(1377W Ø75mm / 1378Z Ø100mm / 1379C Ø150mm)**.

Code: **1377W / 1378Z / 1379C**



Yellow Drain Tracing Dye For tracing the direction of flow or to where a drain pipe runs. Recommended dilution rates at www.4pipetools.com (**1265H approx. 112g / 1271A approx. 227g**).

Code: **1265H / 1271A**



Drain Testing Smoke For testing drains etc. Naked flame required to ignite. Works under water. Approx volume 300m^3. Burn time approx 90s.

Code: **1462G**



Nylon Test Plugs Used for blocking off drain pipes and for air testing with 1/2in BSP outlet **(1375Q Ø42mm / 1376T 50mm / 1380F Ø63mm)**.

Code: **1375Q / 1376T / 1380F**



Universal Flexible Test Plug Use for blocking off and air testing pipes with 174Z. With central mandrel, central nipple is for connection to U Gauge **(Ø89-Ø150mm)**.

Code: **1474R**



Green Drain Tracing Dye For tracing the direction of flow or to where a drain pipe runs. Recommended dilution rates at www.4pipetools.com (**1264E approx. 112g / 1270X approx. 227g**).

Code: **1264E / 1270X**



Blue Drain Tracing Dye For tracing the direction of flow or to where a drain pipe runs. Recommended dilution rates at www.4pipetools.com (**1263B approx. 112g / 1269T approx. 227g**).

Code: **1263B / 1269T**



Red Drain Tracing Dye For tracing the direction of flow or to where a drain pipe runs. Recommended dilution rates at www.4pipetools.com (**1261V approx. 112g / 1268Q approx. 227g**).

Code: **1261V / 1268Q**



Fluorescein Drain Tracing Dye For tracing the direction of flow or to where a drain pipe runs. Fluoresces under black light - does not require UV light. (**1260S approx. 112g / 1267N approx. 227g**).

Code: **1260S / 1267N**