
Geberit electrofusion coupling





Example image

APPLICATION PURPOSES

- For site drainage
- For building drainage
- For high-tensile, permanent connection of pipes and fittings

CHARACTERISTICS

- Can be welded with Geberit electrofusion tools
- UV-resistant

TECHNICAL DATA

Installation temperature	-10 – +40 °C
Product material	PE-HD

INFO

- Can be welded with Advance Welding AW-315G electrofusion machine

Art. no.	DN	d, ø mm	D cm	E cm	H cm	X cm
These articles are suitable for the following system: **Geberit HDPE**						
360.771.16.1	40	40	5.2	2.8	6	0.3
361.771.16.1	50	50	6.2	2.8	6	0.3
363.771.16.1	56	56	6.8	2.8	6	0.3
364.771.16.1	60	63	7.6	2.8	6	0.3

Art. no.	DN	d, ø mm	D cm	E cm	H cm	X cm
365.771.16.1	70	75	8.9	2.8	6	0.3
366.771.16.1	90	90	10.4	2.8	6	0.3
367.771.16.1	100	110	12.5	2.8	6	0.3
368.771.16.1	125	125	14.2	2.8	6	0.3
369.771.16.1	150	160	17.8	2.8	6	0.3
These articles are suitable for the following system: **Geberit Silent-db20**						
363.771.16.1	56	56	6.8	2.8	6	0.3
364.771.16.1	60	63	7.6	2.8	6	0.3
365.771.16.1	70	75	8.9	2.8	6	0.3
366.771.16.1	90	90	10.4	2.8	6	0.3
367.771.16.1	100	110	12.5	2.8	6	0.3
369.771.16.1	150	160	17.8	2.8	6	0.3