415V industrial fuselinks – offset bolted contacts (contd)

Fixing centres, mm	BS88 ref	Rating, In Normal (A)	Motor (A)	Dimensional equivalents GEC/Lawson	Brush/Hawker	Bussmann/ Dorman	Eaton list number
	–	125	–	TFP125	125M14	DEO125	**125SD6**
		160	–	TFP160	160M14	DEO160	**160SD6**
		200	–	TFP200	200M14	DEO200	**200SD6**
			250	TFP200M250	200M250M14	DEO200M250	**200SD6M250**
			315	–	–	–	**200SD6M315**

These industrial bolted pattern fuselinks are of two types – with offset contacts of ratings 2–200A and with centre contacts of ratings 2–1250A.

They are available to BS references A1 to A4, B1 to B4, C1 to C3, D1 and in certain other sizes.

415V industrial fuselinks – centre bolted contacts

20SE3



- S-Type compact industrial bolted pattern fuselinks with centre contacts. ASTA 20 Certified or tested to BS EN 60269-1 (BS88-1) or BS88-2 for a breaking capacity of 80 kA at 415V a.c.

Fixing centres, mm	BS88 ref	Rating In Normal (A)	Motor	Dimensional equivalents GEC/Lawson	Brush/Hawker	Bussmann/Dorman	Eaton list number
97	–	2	–	TB2	2KO8	AC2	**2SE3**
		4	–	TB4	4KO8	AC4	**4SE3**
		6	–	TB6	6KO8	AC6	**6SE3**
		10	–	TB10	10KO8	AC10	**10SE3**
		16	–	TB16	16KO8	AC16	**16SE3**
		20	–	TB20	20KO8	AC20	**20SE3**
		25	–	TB25	25KO8	AC25	**25SE3**
		32	–	TB32	32KO8	AC32	**32SE3**
111	–	2	–	TBC2	2KO9	AD2	**2SF3**
		4	–	TBC4	4KO9	AD4	**4SF3**
		6	–	TBC6	6KO9	AD6	**6SF3**
		10	–	TBC10	10KO9	AD10	**10SF3**
		16	–	TBC16	16KO9	AD16	**16SF3**
		20	–	TBC20	20KO9	AD20	**20SF3**
		25	–	TBC25	25KO9	AD25	**25SF3**

32SF3



		32	–	TBC32	32KO9	AD32	**32SF3**
97	–	40	–	TB40	40KO8	BC40	**40SE4**
		50	–	TB50	50KO8	BC50	**50SE4**
		63	–	TB63	63KO8	BC63	**63SE4**
97	–	63	80	–	–	–	**63SE4M80**
			100	–	–	–	**63SE4M100**
111	B1	40	–	TBC40	40KO9	BD40	**40SF4**
		50	–	TBC50	50KO9	BD50	**50SF4**
		63	–	TBC63	63KO9	BD63	**63SF4**
			80	–	–	–	**63SF4M80**
			100	–	–	–	**63SF4M100**
		80	–	TC80	80LO9	CD80	**80SF5**
		100	–	TC100	100LO9	CD100	**100SF5**
			125	TC100M125	100M125LO9	CD100M125	**100SF5M125**
			160	TC100M160	100M160LO9	CD100M160	**100SF5M160**
			200	TC100M200	100M200LO9	CD100M200	**100SF5M200**
	B2	125	–	TF125	125MO9	DD125	**125SF6**
		160	–	TF160	160MO9	DD160	**160SF6**

200SF6



		200	–	TF200	200MO9	DD200	**200SF6**
			250	TF200M250	200M250M09	DD200M250	**200SF6M250**
			315	–	–	–	**200SF6M315**
	B3	250	–	TKF250	250NO9	ED250	**250SF7**
		315	–	TKF315	315NO9	ED315	**315SF7**
			400	–	–	–	**315SF7M400**
133	–	250	–	TKM250	250N11	EFS250	**250SG7**
		315	–	TKM315	315N11	EFS315	**315SG7**

400SH8



630SY9



1250SJ11



415V industrial fuselinks – centre bolted contacts (contd)

Fixing centres, mm	BS88 ref	Rating In Normal (A)	Motor (A)	Dimensional equivalents GEC/Lawson	Brush/Hawker	Bussmann/Dorman	Eaton list number
111	B4	355	–	TMF355	355PO9	ED355	**355SF8**
		400	–	TMF400	400PO9	ED400	**400SF8**
			500	TMF400M500	–	ED400M500	**400SF8M500**
133/184	C1	355	–	TM355	355P11	EF355	**355SH8**
		400	–	TM400	400P11	EF400	**400SH8**
133/184	C2	450	–	TTM450	450R11	FF450	**450SH9**
		500	–	TTM500	500R11	FF500	**500SH9**
		560	–	TTM560	560R11	FF560	**560SH9**
		630	–	TTM630	630R11	FF630	**630SH9**
165/229	–	450	–	TT450	450R12	FG450	**450SY9**
		500	–	TT500	500R12	FG500	**500SY9**
		630	–	TT630	630R12	GG630	**630SY9**
133/184	C3	710	–	TLM710	700S11	GF710	**710SH10**
		800	–	TLM800	800S11	GF800	**800SH10**
165/229	–	710	–	TLT710	700S12	GG700	**710SY10**
		800	–	TLT800	800S12	GG800	**800SY10**
149	D1	1000	–	TXU1000	1000U44	GH1000	**1000SJ11**
		1250	–	TXU1250	1250U44	GH1250	**1250SJ11**

20SN2



SN type offset blade fuselinks

- ASTA 20 Certified or tested to BS EN 60269-1 (BS88-1) and BS88-6 for a breaking capacity of 80 kA at 415V a.c. For use in industrial and commercial installations.

Overall length, mm	Overall dia. mm	Rating In Normal (A)	Motor (A)	Equivalents GEC/Lawson	Brush/Hawker	Bussmann/Dorman	Eaton list number
60	14	2	–	NS2	2FO6	NSD2	**2SN2**
		4	–	NS4	4FO6	NSD4	**4SN2**
		6	–	NS6	6FO6	NSD6	**6SN2**
		10	–	NS10	10FO6	NSD10	**10SN2**
		16	–	NS16	16FO6	NSD16	**16SN2**
		20	–	NS20	20FO6	NSD20	**20SN2**
			25	NS20M25	20M25FO6	NSD20M25	**20SN2M25**
			32	NS20M32	20M32FO6	NSD20M32	**20SN2M32**
		25	–	NS25	25FO6	NSD25	**25SN2**
		32	–	NS32	32FO6	NSD32	**32SN2**
58	17.5	32	40	NS32M40	–	NSD32M40	**32SN2M40**
			50	NS32M50	–	NSD32M50	**32SN2M50**
			63	NS32M63	–	NSD32M63	**32SN2M63**