Datasheet: CB2

Connector Blocks / Connector Blocks

100A 2x5 Way 25mm Connector Block DP

CB Connector Boxes - Torque setting

Model	Screw Size	Torque (Nm) - Ref Standard EN 60998-2-1
CB1	M6	2.5
CB2	M6	2.5
CB3	M8	3.5
CB6	M8	3.5
CB9	M8	3.5

Technical Specification

Product Code	CB2
Feature 1	Black phenolic urea
Feature 2	Easy knock out entries
Feature 3	Lids can be sealed for security
Feature 4	Conforms to BS EN60998-1 & BS EN60998-2-1
Barcode	5012739616815
CE	Y
Colour	Black
Company DUNS Number	216156018
Country of Origin	China
Current (I)	100
Finish body	Natural smooth
Greenbrook Guarantee (Years)	1
HS Code	8536901000
Ingress Protection (IP)	IP20
Installation method	Surface

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

Datasheet: CB2

Materials Main Body	Urea Phenolic
Min Order Qty	10
No of Poles	Double
Operating Temperature Range max C	40
Operating Temperature Range min C	-10
Package Product Max. Length (mm)	330
Package Product Max. Height (mm)	95
Package Product Max. Width (mm)	132
Package Product Weight gross (g)	3076
Product (only) Max. Depth (mm)	55
Product (only) Max. Height (mm)	89
Product (only) Max. Width (mm)	65
Product Weight net (g)	290
Sales Pack Qty	10
StatusCode	Active
Torque Setting	2.5NM
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26