GREENBROOK

Datasheet: 20GMH

Cable Management / Conduit Accessories

Male Hook malleable Galv 20mm



Technical Specification

Product Code	20GMH
Feature 1	Galvanised steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739612930
CE	Y
Colour	Self Colour
Company DUNS Number	216156018
Corrosion Test	Y
Country of Origin	China
Finish body	Hot dip Galvanised
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

Datasheet: 20GMH

HS Code	7318130090
Installation method	Surface mount
Materials Main Body	Malleable Iron
Min Order Qty	25
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	25
Package Product Max. Length (mm)	188
Package Product Max. Height (mm)	65
Package Product Max. Width (mm)	188
Package Product Weight gross (g)	1874
Product Weight net (g)	71
Sales Pack Qty	25
StatusCode	Active
Thread Diameter	M20
Thread Diameter Ø	M20
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26