GREENBROOK

Datasheet: 25SCME

Cable Management / Conduit Accessories

ME Lockring SC 25mm



Technical Specification

Product Code	25SCME
Feature 1	Mild Steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739613500
CE	Y
Colour	Brass
Company DUNS Number	216156018
Country of Origin	India
Finish body	Self Coloured
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1
HS Code	7318190090
Installation method	Lock nut
Material Thickness	2.87
Materials Main Body	Brass

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

GREENBROOK

Datasheet: 25SCME

Min Order Qty	100
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	100
Package Product Max. Length (mm)	140
Package Product Max. Height (mm)	50
Package Product Max. Width (mm)	120
Package Product Weight gross (g)	1039
Product (only) Max. Width (mm)	25 dia
Product Weight net (g)	9
Sales Pack Qty	100
Standards	BS EN 61386-21
StatusCode	Active
Thread Diameter	M25
Thread Diameter Ø	M25
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26