GREENBROOK

Datasheet: 25G2N

Cable Management / Malleable Conduit Boxes

Conduit Box Through Galv 25mm



Technical Specification

Product Code	25G2N
Feature 1	Galvanised steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739642982
Cable Hole Ø	25
CE	Y
Colour	Self Colour
Company DUNS Number	216156018
Corrosion Test	Y
Country of Origin	China
Finish body	Hot dip Galvanised
Fixings supplied with product	N
Galv Plating Thickness	>45µm
Greenbrook Guarantee (Years)	1
HS Code	7307191090
Ingress Protection (IP)	IP30
Installation method	Surface mount
Material Thickness	2
Materials Main Body	Malleable Iron
Min Order Qty	10

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

GREENBROOK

Datasheet: 25G2N

Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	10
Package Product Max. Length (mm)	190
Package Product Max. Height (mm)	75
Package Product Max. Width (mm)	190
Package Product Weight gross (g)	2506
Product (only) Max. Height (mm)	25
Product (only) Max. Width (mm)	65 Dia
Product Weight net (g)	250
Sales Pack Qty	10
StatusCode	Active
Thread Diameter	M25
Thread Diameter Ø	M25 / M4
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26