SAFETY RELIEF VALVES - SERIES 311 & 312

311430



WRAS APPROVED PRODUCT

CE marked 1115 UK CA 0086

kiwa approved UK WATER REGULATION 4

SAFETY RELIEF VALVES SERIES 311

Ref no	Size	Connections	Pressure	Gauge	
311415	½″ x ½″	F x F BSP	1.5 bar	No	50
311425	½″ x ½″	F x F BSP	2.5 bar	No	50
311430	½″ x ½″	F x F BSP	3 bar	No	50
311435	½″ x ½″	F x F BSP	3.5 bar	No	50
311450	½″ x ½″	F x F BSP	5 bar	No	50
311460	½″ x ½″	F x F BSP	6 bar	No	50
311470	½″ x ½″	F x F BSP	7 bar	No	50
311480	½″ x ½″	F x F BSP	8 bar	No	50
311525	¾″ x ¾″	F x F BSP	2.5 bar	No	50
311530	¾″ x ¾″	F x F BSP	3 bar	No	50
311560	¾″ x ¾″	F x F BSP	6 bar	No	50
311570	¾″ x ¾″	F x F BSP	7 bar	No	50
311580	¾″ x ¾″	F x F BSP	8 bar	No	50

SPECIFICATION

- Medium: Water and air
- Temperature range: 5°c - 110°c
- Set pressure range: 1.5 - 8 bar
- Max working pressure (static): 10 bar
- PED category: IV

312430



WRAS APPROVED PRODUCT

CE marked 1115 UK CA 0086

kiwa approved UK WATER REGULATION 4

SAFETY RELIEF VALVES SERIES 312

Ref no	Size	Connections	Pressure	Gauge		
312405 CST	½″ x ½″	M x F BSP	4 bar	No	50	1600
312020 CST	½" x ½"	F x F BSP	10 bar	No	44	2904
312425	½″ x ½″	M x F BSP	2.5 bar	No	50	2000
312430	½″ x ½″	M x F BSP	3 bar	No	50	2000
312460	½″ x ½″	M x F BSP	6 bar	No	50	2000
312470	½″ x ½″	M x F BSP	7 bar	No	50	2000
312480	½″ x ½″	M x F BSP	8 bar	No	50	2000
A312401 CST	½″ x ½″	Pushfit x F BSP	3 bar	No	65	2000
A312438 CST	½″ x ½″	Pushfit x M BSP	3 bar	No	65	3696

SPECIFICATION

- Medium: Water and air
- Temperature range: 5°c - 110°c
- Set pressure range: 2.5 - 10 bar
- Max working pressure (static): 10 bar
- PED category: IV

To place an order T: 01785 218222 E: tradesales@altecnic.co.uk (Trade)

SAFETY RELIEF VALVES - SERIES 313 & 314

SAFETY RELIEF VALVES SERIES 313

Ref no	Size	Connections	Pressure	Gauge		
313425	½″ x ½″	F x F BSP	2.5 bar	Yes	50	1800
313430	½″ x ½″	F x F BSP	3 bar	Yes	50	1800
313460	½″ x ½″	F x F BSP	6 bar	Yes	50	1800
313470	½″ x ½″	F x F BSP	7 bar	Yes	50	1800
313480	½″ x ½″	F x F BSP	8 bar	Yes	50	1800
313525	¾″ x ¾″	F x F BSP	2.5 bar	Yes	50	1800
313530	¾″ x ¾″	F x F BSP	3 bar	Yes	50	1800
313560	¾″ x ¾″	F x F BSP	6 bar	Yes	50	1800
313570	¾″ x ¾″	F x F BSP	7 bar	Yes	50	1800
313580	¾″ x ¾″	F x F BSP	8 bar	Yes	50	1800

SPECIFICATION

- Medium: Water and air
- Temperature range: 5°c - 110°c
- Set pressure range: 2.5 - 8 bar
- Max working pressure (static): 10 bar
- PED category: IV

313430



WRAS APPROVED PRODUCT

CE marked 1115 UK CA 0086

kiwa approved UK WATER REGULATION 4

SAFETY RELIEF VALVES SERIES 314

Ref no	Size	Connections	Pressure	Gauge		
314425	½″ x ½″	M x F BSP	2.5 bar	Yes	50	1800
314430	½″ x ½″	M x F BSP	3 bar	Yes	50	1800
314460	½″ x ½″	M x F BSP	6 bar	Yes	50	1800
314480	½″ x ½″	M x F BSP	8 bar	Yes	50	1800
A314437 CST	½″ x ½″	M x F BSP	3 bar	Port only	56	3696

SPECIFICATION

- Medium: Water and air
- Temperature range: 5°c - 110°c
- Set pressure range: 2.5 - 8 bar
- Max working pressure (static): 10 bar
- PED category: IV

A314437 CST



WRAS APPROVED PRODUCT

CE marked 1115 UK CA 0086

kiwa approved UK WATER REGULATION 4

T: 01785 218208 E: oemsales@altecnic.co.uk (OEM) T: 01785 218210 E: specifications@altecnic.co.uk (Specification)