GRID-IT Modules

Push On/Off Switches

3A Intermediate
Push On/Off Module

Tungsten Filament and Halogen
Rating: Maximum 3A per gang



Pack Quantity: 5 **Minimum Wall Box Depth:** 35mm **British Standard:** BS 5733	White/White **I DIP WH**

6A 2 Way
Push On/Off Switch Module

Tungsten Filament and Halogen
Rating: Maximum 6AX per gang



Pack Quantity: 5 **Minimum Wall Box Depth:** 35mm **British Standard:** BS 60669-1	White/White **I DPS WH**

Resistive Leading Edge Push On/Off 2 Way Switching Dimmers

400W 2 Way
Dimmer Module

Tungsten Filament and Halogen
Rating: Minimum 40W per gang
Tungsten Filament Rating: Maximum 400W per gang
Halogen Rating: Maximum 300W per gang

Note: Tungsten Filament GU10 Lamps must be branded with a Fused Base.
Note: When using mains voltage halogen lamps - dimmers should be de-rated by 25%.
Note: When dimming LED lamps de-rate by 75% - please contact our Technical Department for compatibility.



Pack Quantity: 5 **Minimum Wall Box Depth:** 35mm **British Standard:** BS 60669-2-1	White/White **I D40 WH**

High Frequency Ballast Controller Module

1-10V DC
High Frequency Ballast
Controller Module (No Off)

Tungsten Filament and Halogen
Rating: Max. 50 Ballasts per Controller 1-10V
DC Control - NOT for connection to 230V Mains.
Only to be used in conjunction with a 10A or 20A 2 Way Rocker Switch.



Pack Quantity: 5 **Minimum Wall Box Depth:** 35mm **British Standard:** BS 60669-2-1	White/White **I DHF10V WH**