GREENBROOK

Datasheet: 20G5N

Cable Management / Malleable Conduit Boxes

Conduit Box Angle Galv 20mm



Technical Specification

Product Code	20G5N
Feature 1	Galvanised steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739642937
Cable Hole Ø	20
CE	Y
Colour	Self Colour
Company DUNS Number	216156018
Corrosion Test	Y
Country of Origin	China
Finish body	Hot dip Galvanised
Fixings supplied with product	N
Galv Plating Thickness	>45µm
Greenbrook Guarantee (Years)	1
HS Code	7307191090
Ingress Protection (IP)	IP30
Installation method	Surface mount
Material Thickness	2
Materials Main Body	Malleable Iron
Min Order Qty	10

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26

Datasheet: 20G5N

Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	10
Package Product Max. Length (mm)	188
Package Product Max. Height (mm)	65
Package Product Max. Width (mm)	180
Package Product Weight gross (g)	2239
Product (only) Max. Height (mm)	25
Product (only) Max. Width (mm)	65 Dia
Product Weight net (g)	215
Sales Pack Qty	10
StatusCode	Active
Thread Diameter	M20
Thread Diameter Ø	M20 / M4
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/03/26