Triflow Solder Ring Range

Conex | Bänninger



Triflow Solder Ring Range



Conex | Bänninger
Triflow Solder Ring

Triflow Solder Ring fittings contain lead-free solder complying with EN 29453 and ISO 9453. When heat is applied, the sufficient layer of lead-free solder fills the gap between the tube and fitting by capillary action to form a mechanically strong, leak-proof joint without the need for external solder application.

Triflow Solder Ring fittings are manufactured in accordance with EN 1254-1 and 4. They are available in sizes 6-66.7mm and are suitable for connecting copper tubes in accordance with EN 1057. Imperial copper tube to BS 659 in sizes 3/8", 2" and 2.1/2" can be readily joined using 12mm, 15mm, 54mm and 66.7mm fittings respectively.

To counteract the dezincification problem, Triflow Solder Ring fittings are manufactured from high-grade copper, red brass or dezincification resistant (DZR) brass.

Applications & Technical Information	
Drinking water	Y
Sanitary water	Y
Heating and chilled water systems	Y
Compressed air	Y
LPG and Natural Gas	Y
Available Sizes	6 - 67mm
Operating Parameters 6-54mm	16 bar @30°C 10 bar @ 65°C 7 bar @ 95°C 6 bar @ 110°C
Warranty	25 years
Material	Copper, DZR, Red Brass

For more details contact our technical team.

SOLDER RING ASSEMBLY INSTRUCTIONS:

Tools required:

Tube cutter, deburring tool, abrasive cloth, flux and blow lamp.

Assembly

- Ensure the copper tube and fitting sizes are compatible. Cut the tube end square, and ensure it retains its shape.
- Deburr the tube, both inside and outside.
- Clean tube with an abrasive cloth, and fitting socket with a wire brush.
- Apply a thin layer of flux to the tube, and to the fitting socket.
- Insert the tube into the fitting until the tube stop is reached. Rotate the tube or fitting and remove excess flux where possible
- Light the blow lamp, and heat the fitting socket until the flux starts to boil. Keep the flame moving over the fitting until a ring of solder appears at the mouth of the socket. Do not provide excessive heat or additional solder.
- Remove the blow lamp, allow to cool and wipe the joint(s) with a damp cloth to remove flux residues.
- Flush all residues out of the system.



Demounting

- This fitting system is not demountable.

Conex | Bänninger
Triflow Solder Ring

TP3LC

Straight Male Connector

Copper x Male Thread (Parallel)



ITEM	SIZE	PACK
TP03151/4	15 x 1/4"	25
TP03153/8	15 x 3/8"	10

TP5

Tank Connector

Copper x Female Thread



ITEM	SIZE	PACK
TP05151/2	15 x 1/2"	25
TP05223/4	22 x 3/4"	10
TP05281/0	28 x 1"	5
TP053511/4	35 x 1.1/4"	1
TP054211/2	42 x 1.1/2"	1
TP05542/0	54 x 2"	1

*A range means fast moving products.

Conex | Bänninger
Triflow Solder Ring

TP6

Fitting Reducer

Male Copper x Copper



ITEM	SIZE	PACK	
TP061008	10 x 8mm	10	
TP061508	15 x 8mm	25	
TP061510	15 x 10mm	25	
TP061512	15 x 12mm	25	
TP062212	22 x 12mm	25	
TP062215	22 x 15mm	25	A
TP062815	28 x 15mm	10	
TP062822	28 x 22mm	10	
TP063515	35 x 15mm	10	
TP063522	35 x 22mm	10	
TP063528	35 x 28mm	10	
TP064215	42 x 15mm	5	
TP064222	42 x 22mm	5	
TP064228	42 x 28mm	5	
TP064235	42 x 35mm	5	
TP065415	54 x 15mm	2	
TP065422	54 x 22mm	2	
TP065428	54 x 28mm	2	
TP065435	54 x 35mm	2	
TP065442	54 x 42mm	2	
TP066728	67 x 28mm	1	
TP066735	67 x 35mm	1	
TP066742	67 x 42mm	1	
TP066754	67 x 54mm	1	

*A range means fast moving products.

SALES: +44 (0)121 557 2831 FAX: +44 (0)121 520 8778 WEB: www.conexbanninger.com EMAIL: sales@ibpgroup.com