Sleeve Anchors

Sleeve Anchors

- General purpose medium duty anchor for use in concrete, brick and stone
- A through fixing with thin expansion sleeve for low stress in base material
- A very versatile anchor
- Zinc plated and yellow passivated

Applications
Railings, parapets, ducting, light steel works, bracketry, cable trays, timber doors, window frames and satellite dishes.

Hexagon Nut Sleeve Anchors



Range Information

Product Code	Size mm	Hole Size mm	Max Fixture Thickness mm	Min Hole Depth in Substrate mm	Bolt Diameter	Min Penetration Depth mm	Washered Nut Diameter mm	Unit Qty
125-300-012	8 x 40	8	5	40	M6	35	14	100
125-300-020	8 x 65	8	30	40	M6	35	14	50
125-300-036	10 x 50	10	10	45	M8	40	18	50
125-300-045	10 x 77	10	37	45	M8	40	18	50
125-300-050	10 x 97	10	57	45	M8	40	18	50
125-300-060	12 x 75	12	25	55	M10	50	21.5	50
125-300-065	12 x 99	12	49	55	M10	50	21.5	25
125-300-072	12 x 129	12	79	55	M10	50	21.5	25
125-300-082	16 x 111	16	56	65	M12	55	26	10
125-300-090	16 x 147	16	92	65	M12	55	26	10

Hexagon Bolt Sleeve Anchors



Range Information

Product Code	Size mm	Hole Size mm	Max Fixture Thickness mm	Min Hole Depth in Substrate mm	Bolt Diameter	Min Penetration Depth mm	Washer Diameter mm	Unit Qty
125-300-210	8 x 60	8	10	50	M6	50	18.5	100
125-300-220	10 x 60	10	15	45	M8	50	20	50
125-300-230	10 x 80	10	35	50	M8	70	20	50
125-300-240	12 x 70	12	15	55	M10	60	24.5	25
125-300-250	12 x 100	12	40	65	M10	80	24.5	25
125-300-270	16 x 110	16	40	70	M12	80	24.5	10

Wire Hanger

Ceiling Hanger



Tie Wire

- Expansion anchor for securing suspension wires in concrete, solid brickwork or stone
- Steel zinc plated and yellow passivated

Applications
Ideal for fixing suspended ceilings.

Range Information

Product Code	Size mm	Anchor Hole Diameter mm	Anchor Length mm	Eye Diameter mm	Min. Hole Depth mm	Unit Qty
125-320-005	6 x 55	6	55	5.3	40	200